

CLAIMS:

What is claimed is:

1. Apparatus for bridging a fuse of an electronic device comprising:
a base; and
5 a conductive element mounted on the base, which may be brought into contact with and bridge a fuse.

2. The apparatus of claim 1 and further comprising a plurality of conductive elements mounted on the base, at least some of which may be brought into contact with and bridge a fuse.
10

3. The apparatus of claim 2 wherein the conductive elements are substantially parallel and in spaced-apart relation.
15

4. The apparatus of claim 2 wherein the base is resilient compressive material.
20

5. The apparatus of claim 2 wherein the base is insulating material.
25

6. The apparatus of claim 3 wherein the base is resilient, compressive, insulating material.
30

7. The apparatus of claim 3 wherein the plurality of conductive elements lies within the periphery of the base.
35

8. Apparatus for testing an electrical device which includes a fuse comprising:
a thermal head;
a base mounted on the thermal head;
a conductive element mounted to the base, which may be brought into contact with and bridge a fuse with the thermal head adjacent an electrical device.

9. The apparatus of claim 8 and further comprising a plurality of conductive elements mounted on the base, at least some of which may be brought into contact with and bridge a fuse.

10. The apparatus of claim 9 wherein the conductive elements are substantially parallel and in spaced-apart relation.

11. The apparatus of claim 10 wherein the base is resilient, compressive, insulating material.
12. The apparatus of claim 11 wherein the plurality of conductive elements lies within 5 the periphery of the base.
13. The apparatus of claim 12 and further comprising an electrical device which includes a fuse.
- 10 14. The apparatus of claim 13 wherein the electrical device further comprises at least one resistor operatively associated with the fuse.

15